


Value-line Step Cover



.125 mil nominal thickness with 1.5" nose.
Available in fine, medium and coarse texture in standard colors only.

- Value priced
- Easily cut to fit using common tools
- Appropriate for many residential applications

5-year limited warranty

Typical Physical Properties

Property	Specification	Test Method
Flexural Strength, psi, 77°F	20,592	ASTM - D790
Flexural Strength, 190°F	7,722	ASTM - D790
Tensile Strength, psi, 77°F	11,880	ASTM - D638
Tensile Strength, psi, 150°F	9,966	'
Tensile Strength, 190, 190°F	7920	'
Hardness, Barcol	36	ASTM - D2583
Impact Resistance (Izod Test)	3.0ft-lb/in	ASTM - D256
Coefficient of Friction (medium non -slip profile)	Dry - .93 Wet - .82	ASTM - 1028
Flammability (Flame Spread) Test HLT HLT-15 Rating	10 (unfilled) Class I 100 AEB<1.0 CM ATB< 5 Sec.	ASTM -E84 ASTM-D635
Oxygen Index UL	360 Min V-O at 0.060 inches	ASTM D-2863
*FLAMMABILITY: Reference to specific laboratory scale test methods, results or numerical flame spread data is not intended to reflect possible hazards presented by these materials under actual fire conditions.		

RezCast product nominal thickness .125 mils in. overall; specifications subject to change without notice.

Note: Test results based on .125 laminate thickness