


RezCast® Industrial Step Cover



.250 mil nominal thickness with 2" nose and optional safety stripe in a contrasting color. Available in fine, medium and coarse texture in standard or premium colors.

- Thicker construction for heavy traffic demands.
- Flexural Strength 31,800 PSI
- Highly resistant to chemical exposure
- 10-year limited warranty

Typical Physical Properties

Property	Specification	Test Method
Flexural Strength, psi, 77°F	31,200	ASTM - D790
Flexural Strength, 190°F	11,700	ASTM - D790
Tensile Strength, psi, 77°F	18,000	ASTM - D638
Tensile Strength, psi, 150°F	15,100	'
Tensile Strength, 190, 190°F	12,000	'
Hardness, Barcol	55	ASTM - D2583
Impact Resistance (Izod Test)	4.5 ft-lb/in	ASTM - D256
Coefficient of Friction	Dry - .93	ASTM - 1028
(medium non -slip profile)	Wet - .82	
Flammability (Flame Spread) Test HLT	10 (unfilled)	Class I
HLT-15 Rating	100	ASTM -E84
	AEB<1.0 CM	ASTM-D635
	ATB< 5 Sec.	
Oxygen Index	360 Min	ASTM D-2863
UL	V-O at 0.060 inches	
*FLAMMABILITY: Reference to specific laboratory scale test methods, results or numerical flame spread data is not intended to reflect possible hazards presented by these materials under actual fire conditions.		

RezCast product nominal thickness .187 mils in. overall; specifications subject to change without notice.

Note: Test results based on .125 laminate thickness