


S-SC Commercial Step Cover



.187 mil nominal thickness with 1.5" nose and safety stripe in a contrasting color. Available in fine, medium and coarse texture in standard or premium colors.

- Available in many colors and textures
- Meets UL 900 Class 1 flammability standard
- Best choice for most applications
- 10-year limited warranty

Typical Physical Properties

Property	Specification	Test Method
Flexural Strength, psi, 77°F	23,400	ASTM - D790
Flexural Strength, 190°F	8775	ASTM - D790
Tensile Strength, psi, 77°F	13,500	ASTM - D638
Tensile Strength, psi, 150°F	11,325	
Tensile Strength, 190, 190°F	9,000	
Hardness, Barcol	42	ASTM - D2583
Impact Resistance (Izod Test)	4 ft-lb/in	ASTM - D256
Coefficient of Friction	Dry - .93	ASTM - 1028
(medium non -slip profile)	Wet - .82	
Flammability (Flame Spread) Test HLT	10 (unfilled)	Class I
HLT-15 Rating	100	ASTM -E84
	AEB<1.0 CM	ASTM-D635
	ATB< 5 Sec.	
Oxygen Index	360 Min	ASTM D-2863
UL	V-O at 0.060 inches	
<p>*FLAMMABILITY: Reference to specific laboratory scale test methods, results or numerical flame spread data is not intended to reflect possible hazards presented by these materials under actual fire conditions.</p>		

RezCast product nominal thickness .187 mils in. overall; specifications subject to change without notice.

Note: Test results based on .125 laminate thickness