

RezCast® ADA Step Cover



.250 or .187 mil nominal thickness with 1.5" nose and safety stripe in a contrasting color. Custom sizes. Available in fine, medium and coarse texture in standard or premium colors. Complies to ADA/CALDAG standards (1133B.4.4, 1133B.4.5) for the visually impaired

- Available in Commercial or Industrial thickness
- 10-year limited warranty

Typical Physical Properties

Property	Specification	Test Method
Flexural Strength, psi, 77°F	31,200	ASTM - D790
Flexural Strength, 190°F	11,700	ASTM - D790
Tensile Strength, psi, 77°F	18,000	ASTM - D638
Tensile Strength, psi, 150°F	15,100	'
Tensile Strength, 190, 190°F	12,000	'
Hardness, Barcol	55	ASTM - D2583
Impact Resistance (Izod Test)	4.5 ft-lb/in	ASTM - D256
Coefficient of Friction (medium non -slip profile)	Dry - .93 Wet - .82	ASTM - 1028
Flammability (Flame Spread) Test HLT HLT-15 Rating	10 (unfilled) Class I 100	ASTM -E84
	AEB<1.0 CM ATB< 5 Sec.	ASTM-D635
Oxygen Index UL	360 Min V-O at 0.060 inches	ASTM D-2863

*FLAMMABILITY: Reference to specific laboratory scale test methods, results or numerical flame spread data is not intended to reflect possible hazards presented by these materials under actual fire conditions.

RezCast product nominal thickness .187 mils in. overall; specifications subject to change without notice.

Note: Test results based on .125 laminate thickness